

MONROE TUFLINE[®]

"V"-PLOW SERIES

please clone sky to allot for bleed▲

MONROE TUFLINE MANUFACTURING COMPANY, INC.

P.O. Box 186 • Columbus, MS 39703-0186

Phone (601) 328-8347 • FAX (601) 328-8361

28" SHANK MODELS

MODEL	APPRX WEIGHT	FRAME WIDTH	TRANSPORT WIDTH	SHANK SPACING	SHANKS	HP REQD
3-28-88	1036	88"	7'3"	20-30"	3	60
5-28-120	1552	120"	11'	20"	5	90-100
5-28-142	1618	142"	13'	20-30"	5	90-100
7-28-142	1989	142"	13	20"	7	130-150
7-28-182	2134	182"	16'2"	20-30"	7	130-150
9-28-182	2504	182"	16'2"	20"	9	160-180
7-28-222	2248	222"	18'6"	30"	7	130-150
9-28-222	2619	222"	18'6"	20-30"	9	160-180
11-28-222	2990	222"	18'6"	20"	11	210-240

32" SHANK MODELS

MODEL	APPRX WEIGHT	FRAME WIDTH	TRANSPORT WIDTH	SHANK SPACING	SHANKS	HP REQD
3-32-88	1102	88"	7'3"	20-30"	3	60
5-32-120	1660	120"	11'	20"	5	90-100
5-32-142	1726	142"	13'	20-30"	5	90-100
7-32-142	2139	142"	13	20"	7	130-150
7-32-182	2284	182"	16'2"	20-30"	7	130-150
9-32-182	2695	182"	16'2"	20"	9	160-180
7-32-222	2399	222"	18'6"	30"	7	130-150
9-32-222	2812	222"	18'6"	20-30"	9	160-180
11-32-222	3224	222"	18'6"	20"	11	210-240

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

20" adjustable coulters are available on TUFLINE'S new coulters frame units. This allows easier shank penetration with less topsoil disturbance!



MONROE TUFLINE
"V"-PLOW SERIES

Contact Your Local Farm Equipment Dealer

MONROE TUFLINE
MANUFACTURING COMPANY, INC.
P.O. Box 186 • Columbus, MS 39703-0186
Phone (601) 328-8347
FAX (601) 328-8361
www.monroetuflines.com

Form-VP6/98

www.monroetuflines.com

TUFLINE'S

"V"-Plows are designed to break up hardpan and compaction, allowing greater moisture retention and fertilizer placement to the plant root zone. These tough plows offer heavy 7 x 5" steel tube "V" shape frames creating an easier pull than straight frame subsoilers. All units offer category II and III hitch and fit most category III quick hitch systems. The **TUFLINE** "V"-Plows are available in 3, 5, 7, 9, and 11 shank models with 28" or 32" hi-strength shanks. Shanks are mounted on either 30" pre-fixed space frames or adjustable frames. We also offer a coultter mount frame which employs a 20" coultter blade in front of each shank allowing minimal topsoil disruption. All units offer heat treated wear points and shear bolt protected shank mounts for subsurface obstructions. Reversible hard surfaced points and gauge wheels are offered as an option.

TUFLINE "V"-Plows are part of our complete line of ground engaging and tillage equipment. Our products offer 40 years of proven success and can help make your operation more economical and successful.



MODEL VP7-32-182



TUFLINE offers fixed or adjustable shank spacing with 28" or 32" hi-strength shanks, and heat-treated wear points.



Adjustable Gauge Wheel Kits with 9.5L-15 or 11L-15 implement tires are available as an option.

MONROE TUFLINE[®]

"V"-PLOW SERIES