

Tufline®

SUBSOILERS



SUBSOILERS

MODEL	FRAME WIDTH	SHANK NO./SIZE	SHANK SPACING	MINIMUM* H.P. REQ'D	WEIGHT
1S-24	26"	1-24"	0	30	229#
1S-28	26"	1-28"	0	30	243#
2S-24	49"	2-24"	12"-36"	50	520#
2S-28	49"	2-28"	12"-36"	50	548#
2S-24-60	60"	2-24"	12"-48"	50	556#
2S-28-60	60"	2-28"	12"-48"	50	609#
2S-29-90	80"	2-28"	12"-72"	60	665#
3S-28-90	90"	3-28"	ADJ.	75	1205#
3S-32-90	90"	3-32"	ADJ.	75	1264#

*Horsepower requirements may vary due to different soil conditions.

TUFLINE Subsoilers are quality farm tools designed to fracture the soil so air and water may re-enter and allow better root growth.

Heavy 7"x 5" steel tube frames with 1, 2 or 3 shank options make these units ideal for 30 to 130 horsepower tractors. Hi-strength 1½" thick shank are available in 24", 28" or 32" lengths with 1080 grade heat treated steel points. Both one and two shank models offer category I or II hitch, with the three shank standard with category II.

When soil compaction is a problem, put a TUFLINE Subsoiler to work and see your yield and profits increase!

Monroe Tufline® Manufacturing Company, Inc.

P.O. Box 186 / Columbus, MS 39703-0186
Phone (662) 328-8347 / FAX (662) 328-8361