

Tufline[®] LR SERIES



LR SERIES LANDSCAPE RAKES

TUFLINE'S LR series landscape rakes are quality built units that offer many versatile landscape applications. These rugged rakes allow the operator the ability to perform tough cleanup jobs such as rock and root removal, spreading of topsoil, mulch or crushed rock, and general site grooming for either large or small construction projects. The heavy angle rake tine bar offers dual bolted rake tines which allow added support. The 5160 grade high carbon spring steel tines are heat treated for added strength. The rake support and hitch is constructed with 4" heavy wall tubing and offers both left and right angling or a 360 degree pivot when backfilling is required. Tufline's landscape rakes are available in 5ft, 5½ ft, 6ft and 7ft models. All units offer a standard category 1 hitch, park stand and optional gauge wheel kit.

**MONROE TUFLINE
MANUFACTURING COMPANY, INC.**

P.O. Box 186

Columbus, MS 39703-0186

Phone (662) 328-8347 • FAX (662) 328-8361



▲ Rake Tines are 5160 grade high carbon spring steel and mounted on 1" spacing. The 15" tines are mounted with two bolts for added support.



▲ Quick mounting optional gauge wheel kits offer rake bar height adjustment when "fine tuned" raking applications are required.

SPECIFICATIONS:

Horsepower rating – 15 to 40

Hitch – category 1 Three point

Rake Tines – 15" x 1" x 5/16" Heat treated Spring Steel

Main Frame – 4" Square Steel Tube

4" x 4" x 3/8" Angle Iron

Gauge Wheels – Spring load pivoting caster with 12" tires

Working Widths – 5ft, 5½ ft, 6ft, and 7ft